

## Frequency Processing of Blasts and Earthquakes

In this work, we exploit the difference in time-frequency signatures between blasts and earthquakes, as a possible discriminant. Time-varying instantaneous frequency signals will be computed in two ways:

- 1) We will use the classical method of Taner and Koehler [1]. The instantaneous frequency is obtained by differentiating the instantaneous phase of the analytic signal. If the data is very noisy, then the resulting instantaneous frequency, as a function of time, is not a useful result. When the signal envelope is very small, the instantaneous frequency is amplified incorrectly;
- 2) A two-dimensional frequency map is computed using a novel implementation of the Short-Time Fourier Transform, the Stockwell Transform (ST) [2], which is a form of the continuous wavelet transform [3]. The ST frequency-centroid yields the instantaneous frequency signal, without differentiation.

### References

- [1] Taner, M.T., Koehler, F. "Complex seismic trace analysis", Geophysics, vol. 44, Issue 6, pp.1041-1063 (1979).
- [2] Stockwell, R.G., Mansinha, L. and Lowe, R.P. "Localization of the complex spectrum: the Stransform", IEEE Trans. Signal Processing, Vol. 44, No.4, pp.998-1001, (1996).
- [3] Gibson, P. C., Lamoureux, M. P., Margrave G. F. "Stockwell and Wavelet Transforms", Journal of Fourier Analysis and Applications, December 2006, Volume 12, Issue 6, pp.713-721.

**Primary author:** YEDLIN, Matthew (University of British Columbia)

**Presenter:** YEDLIN, Matthew (University of British Columbia)

**Track Classification:** Theme 2: Events and Their Characterization